


THIS DRAWING AND THE DATA DISCLOSED HEREIN OR HEREWITH IS NOT TO BE REPRODUCED USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF JESS-LINK PRODUCTS CO.,LTD.(JPC)

CUSTOMER DRAWING

REV.	ECN NO.	DESCRIPTION	MDF'D	APP'D	DATE
01		INITIAL DESIGN	Colin	Andrew	11/13/2020
02		ADD PART NO.&UPDATE DATE	Colin	Andrew	03/12/2021

PART NO.	熔斷器額定電流值
PCN2C003RC78-0	315A
PCN2C004RC78-0	100A
PCN2C005RC78-0	250A
PCN2C006RC78-0	400A

NOTE:  
1.儲存溫度Storage temperture: -40°C~+80°C  
2.工作溫度Operating temperature: -40~+125°C;  
3.額定電流Current rating:隨保險絲(Fuse)規格而變動;  
4.額定電壓Operating voltage:Power:DC750V;  
5.防護等級(連接狀態)Protection class:IP67&IP6K9K;  
6.絕緣材料阻燃等級Flame retardant grade of insulating materials:UL94V-0;  
7.使用壽命Durability:50cycle;  
8.帶高壓互鎖Electrical interlock:(HVIL);

RoHS COMPLIANT	HALOGEN FREE	Unit : mm	PROJECTION		JPC connectivity			
		GENERAL TOLERANCES: (UNLESS SPECIFIED)						
		0 = ±.50 0.0 = ±.25 0.00 = ±.15 0.000 = ±.05 0" = ±.2" 0.0" = ±.1"	D.R. 03/18/2021 Colin	TITLE		Mini MSD 插頭 (Customer drawing)		PD./FILE NO. &PRODUCT_NO C20C0012A
			CH.K	SCALE 1:2 SIZE A4		DWG NO. PCN2C003RC78-0		REV. 02
		APV.D	SH,T NO.1 OF 1					